




BEARING CORP.OF AMERICA

95 mm x 130 mm x 18 mm SKF S71919 ACB/P4A angular contact ball bearings

Bearing No. S71919 ACB/P4A



S71919 ACB/P4A Bearing 2D drawings and 3D CAD models

| | |
|---|--------------|
| Size | 130x95x18 mm |
| Bore Diameter | 130 mm |
| Outer Diameter | 95 mm |
| Width | 18 mm |
| d | 95 mm |
| D | 130 mm |
| B | 18 mm |
| d ₁ | 107.94 mm |
| d ₂ | 106.36 mm |
| D ₂ | 120.7 mm |
| r _{1,2} - min. | 1.1 mm |
| r _{3,4} - min. | 0.6 mm |
| a | 40.2 mm |
| d _a - min. | 101 mm |
| d _a - max. | 107.2 mm |
| d _b - min. | 101 mm |
| d _b - max. | 105.7 mm |
| D _a - max. | 124 mm |
| D _b - max. | 126.8 mm |
| r _a - max. | 1 mm |
| r _b - max. | 0.6 mm |
| Basic dynamic load rating - C | 17.2 kN |
| Basic static load rating - C ₀ | 17.6 kN |
| Fatigue load limit - P _u | 0.71 kN |



BEARING CORP.OF AMERICA

| | |
|---------------------------------------|--------------|
| Limiting speed for grease lubrication | 12000 r/min |
| Ball - D_w | 7.144 mm |
| Ball - z | 38 |
| Calculation factor - e | 0.68 |
| Calculation factor - Y_2 | 0.87 |
| Calculation factor - Y_0 | 0.38 |
| Calculation factor - X_2 | 0.41 |
| Calculation factor - Y_1 | 0.92 |
| Calculation factor - Y_2 | 1.41 |
| Calculation factor - Y_0 | 0.76 |
| Calculation factor - X_2 | 0.67 |
| Preload class A - G_A | 105 N |
| Preload class B - G_B | 210 N |
| Preload class C - G_C | 630 N |
| Calculation factor - f | 1.13 |
| Calculation factor - f_1 | 0.99 |
| Calculation factor - f_{2A} | 1 |
| Calculation factor - f_{2B} | 1.02 |
| Calculation factor - f_{2C} | 1.07 |
| Calculation factor - f_{HC} | 1 |
| Preload class A | 147 N/micron |
| Preload class B | 188 N/micron |
| Preload class C | 286 N/micron |
| d_1 | 107.94 mm |
| d_2 | 106.36 mm |
| D_2 | 120.7 mm |
| $r_{1,2}$ min. | 1.1 mm |
| $r_{3,4}$ min. | 0.6 mm |
| d_a min. | 101 mm |



BEARING CORP.OF AMERICA

| | |
|---|----------------|
| d_a max. | 107.2 mm |
| d_b min. | 101 mm |
| d_b max. | 105.7 mm |
| D_a max. | 124 mm |
| D_b max. | 126.8 mm |
| r_a max. | 1 mm |
| r_b max. | 0.6 mm |
| Basic dynamic load rating C | 22.9 kN |
| Basic static load rating C_0 | 28 kN |
| Fatigue load limit P_u | 0.71 kN |
| Attainable speed for grease lubrication | 12000 r/min |
| Ball diameter D_w | 7.144 mm |
| Number of balls z | 38 |
| Preload class A G_A | 105 N |
| Static axial stiffness, preload class A | 147 N/ μ m |
| Preload class B G_B | 210 N |
| Static axial stiffness, preload class B | 188 N/ μ m |
| Preload class C G_C | 630 N |
| Static axial stiffness, preload class C | 286 N/ μ m |
| Calculation factor f | 1.13 |
| Calculation factor f_1 | 0.99 |
| Calculation factor f_{2A} | 1 |
| Calculation factor f_{2B} | 1.02 |
| Calculation factor f_{2C} | 1.07 |
| Calculation factor f_{HC} | 1 |
| Calculation factor e | 0.68 |
| Calculation factor (single, tandem) Y_2 | 0.87 |
| Calculation factor (single, tandem) Y_0 | 0.38 |



BEARING CORP.OF AMERICA

| | |
|---|---------|
| Calculation factor (single, tandem) X_2 | 0.41 |
| Calculation factor (back-to-back, face-to-face) Y_1 | 0.92 |
| Calculation factor (back-to-back, face-to-face) Y_2 | 1.41 |
| Calculation factor (back-to-back, face-to-face) Y_0 | 0.76 |
| Calculation factor (back-to-back, face-to-face) X_2 | 0.67 |
| Mass bearing | 0.64 kg |